

BIZOL Initial Gear Oil GL5 SAE 80W-90

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Issue date: 2/4/2021

Version: 1.0

SDS No: 11524-0016



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : BIZOL Initial Gear Oil GL5 SAE 80W-90

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : Transmission oil

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

BIZOL Germany GmbH
Martin-Buber-Straße 12
14163 Berlin - Germany
T +49 30 804869 0 - F +49 30 804 869 2860
support@bizol.de - www.bizol.com

1.4. Emergency telephone number

Emergency number : +49 30 804869 0 (Mo-Fr 08:00 - 17:00)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Serious eye damage/eye irritation, Category 2 H319

Skin sensitisation, Category 1 H317

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

May cause an allergic skin reaction. Causes serious eye irritation.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS07

Signal word (CLP) :

Warning

Contains :

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentoxide, and salted by amines, C12-14- tert-alkyl ;
Reaction product of 1,3,4-thiadiazolidine-2,5-dithione, formaldehyde and phenol, heptyl derivs.

Hazard statements (CLP) :

H317 - May cause an allergic skin reaction.

H319 - Causes serious eye irritation.

BIZOL Initial Gear Oil GL5 SAE 80W-90

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
SDS No: 11524-0016



Precautionary statements (CLP)

: P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 - Wash hands thoroughly after handling.
P280 - Wear protective gloves, protective clothing, face protection, eye protection.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P501 - Dispose of contents and container to in accordance with local and national regulations.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl	(EC-No.) 931-384-6 (REACH-no) 01-2119493620-38	≥ 1 – < 3	Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318 Skin Sens. 1B, H317 Aquatic Chronic 2, H411
(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines	(CAS-No.) 1213789-63-9 (EC-No.) 627-034-4 (REACH-no) 01-2119473797-19	≥ 0.1 – < 1	Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Asp. Tox. 1, H304 STOT SE 3, H335 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Reaction product of 1,3,4-thiadiazolidine-2,5-dithione, formaldehyde and phenol, heptyl derivs. substance listed as REACH Candidate (Reaction products of 1,3,4-thiadiazolidine-2,5-dithione, formaldehyde and 4-heptylphenol, branched and linear (RP-HP) [with ≥0.1% w/w 4-heptylphenol, branched and linear (4-HPb)]) substance identified as having endocrine disrupting properties	(EC-No.) 939-460-0 (REACH-no) 01-2119971727-23	≥ 0.1 – < 1	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1B, H317 Aquatic Chronic 3, H412

Specific concentration limits:

Name	Product identifier	Specific concentration limits
Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl	(EC-No.) 931-384-6 (REACH-no) 01-2119493620-38	(50 <C ≤ 100) Eye Dam. 1, H318

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general

: Take off immediately all contaminated clothing.

BIZOL Initial Gear Oil GL5 SAE 80W-90

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
SDS No: 11524-0016



First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Attention. Beware, danger of aspiration. Do not give an unconscious person anything to drink. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
------------------------------	--

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	: Toxic fumes may be released. Hydrocarbons. Carbon monoxide. Carbon dioxide. Hydrogen sulfide. Nitrogen oxides. Phosphorus oxides. Toxic pyrolysis products.
--	---

5.3. Advice for firefighters

Firefighting instructions	: Do not allow run-off from fire fighting to enter drains or water courses.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Exclude sources of ignition and ventilate the area. Spills of this product present a serious slipping hazard.
------------------	---

6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing Vapours.
----------------------	---

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Take up liquid spill into absorbent material.
Other information	: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13. Refer to protective measures listed in sections 7 and 8.

BIZOL Initial Gear Oil GL5 SAE 80W-90

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
SDS No: 11524-0016



SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Avoid breathing Vapours. Wear personal protective equipment.
- Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store in a well-ventilated place. Keep cool. Store in a dry place.
- Storage temperature : < 50 °C
- Special rules on packaging : Keep only in original container.
- Storage class (LGK) : LGK 10 - Combustible liquids

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

BIZOL Initial Gear Oil GL5 SAE 80W-90	
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	Destillate (Erdöl), mit Wasserstoff behandelt leichte (C9 – C14 Aliphaten)
AGW (OEL TWA) [1]	Siehe TRGS 900, Nummer 2.9
Peak exposure limitation factor	AGS;Y
Regulatory reference	TRGS900

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

BIZOL Initial Gear Oil GL5 SAE 80W-90

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
SDS No: 11524-0016



Eye protection:

Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Preventive skin protection recommended. This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
protective gloves	Nitrile rubber	6 (> 480 minutes)	0.33		EN ISO 374
protective gloves	Nitrile rubber	2 (> 30 minutes)	0.11		EN ISO 374

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Device	Filter type	Condition	Standard
filtering face piece	A-P2	Short term exposure	

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Yellowish to brownish.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: > 320 °C
Flash point	: > 220 °C DIN ISO 2592
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0.887 – 0.897 g/cm ³ (15 °C)
Solubility	: insoluble in water.
Log Pow	: No data available
Viscosity, kinematic	: 135 mm ² /s (40 °C)
Viscosity, dynamic	: No data available
Explosive properties	: No data available

BIZOL Initial Gear Oil GL5 SAE 80W-90

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
SDS No: 11524-0016



Oxidising properties : No data available
Lower explosive limit (LEL) : 0.6 vol %
Upper explosive limit (UEL) : 6.5 vol %

9.2. Other information

Pourpoint : -27 °C (DIN/ISO 3016)

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Vapour/air-mixtures are explosive at intense warming.

10.5. Incompatible materials

Oxidizing agent.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitisation : May cause an allergic skin reaction.
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

STOT-repeated exposure : Not classified

(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)

STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
------------------------	--

Aspiration hazard : Not classified

BIZOL Initial Gear Oil GL5 SAE 80W-90

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
SDS No: 11524-0016



SECTION 12: Ecological information

12.1. Toxicity

- Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
- Hazardous to the aquatic environment, short-term (acute) : Not classified
- Hazardous to the aquatic environment, long-term (chronic) : Not classified (On basis of test data)

12.2. Persistence and degradability

BIZOL Initial Gear Oil GL5 SAE 80W-90

Persistence and degradability	Not readily biodegradable. Potentially biodegradable.
-------------------------------	---

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Component

Reaction product of 1,3,4-thiadiazolidine-2,5-dithione, formaldehyde and phenol, heptyl derivs.	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
---	---

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

- Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
- Product/Packaging disposal recommendations : Packaging that cannot be cleaned should be disposed of like the product. Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.
- European List of Waste (LoW) code : 13 02 05* - mineral-based non-chlorinated engine, gear and lubricating oils

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

BIZOL Initial Gear Oil GL5 SAE 80W-90

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
SDS No: 11524-0016



14.5. Environmental hazards

Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

14.6. Special precautions for user

Overland transport

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

Inland waterway transport

Not applicable

Rail transport

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains a substance on the REACH candidate list in concentration $\geq 0.1\%$ or with a lower specific limit: Reaction products of 1,3,4-thiadiazolidine-2,5-dithione, formaldehyde and 4-heptylphenol, branched and linear (RP-HP) [with $\geq 0.1\%$ w/w 4-heptylphenol, branched and linear (4-HPbl)] (EC 939-460-0)

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

15.1.2. National regulations

Germany

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1)

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
DOT	Department of Transport

BIZOL Initial Gear Oil GL5 SAE 80W-90

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

SDS No: 11524-0016



TDG	Transportation of Dangerous Goods
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
GHS	Globally Harmonized System of Classification, Labelling and Packaging of Chemicals
IARC	International Agency for Research on Cancer
vPvB	Very Persistent and Very Bioaccumulative
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
CAS	CAS (Chemical Abstracts Service) number
IBC-Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ATE	Acute Toxicity Estimate
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
BCF	Bioconcentration factor
MARPOL 73/78	MARPOL 73/78: International Convention for the Prevention of Pollution From Ships
ADG	Transport of Australian Dangerous Goods
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
ED	Endocrine disrupting properties

BIZOL Initial Gear Oil GL5 SAE 80W-90

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
SDS No: 11524-0016



Other information : Data of sections 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities. The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge. The delivery specifications are contained in the corresponding product sheet. This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

Full text of H- and EUH-statements:	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Eye Irrit. 2	H319	Calculation method
Skin Sens. 1	H317	Calculation method

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.