

Revision date:  
17.06.2021

**BIZOL Leak and Smoke Stop+ o92**

Page 1 of 8

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

BIZOL Leak and Smoke Stop+ o92

**Further trade names**

UFI: 3JE2-R02U-D00G-56D1

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Use of the substance/mixture**

Additive

**1.3. Details of the supplier of the safety data sheet**

Company name:	BIZOL Germany GmbH	
Street:	Martin-Buber-Str. 12	
Place:	D-14163 Berlin	
Telephone:	+49 (30) 804 869-0	Telefax: +49 (30) 804 869-2860
e-mail:	support@bizol.de	
Internet:	www.bizol.com	

**1.4. Emergency telephone number:**

Germany: +49 (30) 804 869-0 (08.00-17.00, Mo-Fr)  
In England and Wales: NHS Direct: 0845 4647 or 111 In Scotland: NHS 24 -  
08454 24 24 24 In Republic of Ireland: 01 809 2166

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**GB CLP Regulation**

Skin Sens. 1; H317  
STOT RE 2; H373  
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

**2.2. Label elements**


**GB CLP Regulation**

**Hazard components for labelling**

dibutyl maleate

**Signal word:** Warning

**Pictograms:**



**Hazard statements**

H317	May cause an allergic skin reaction.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

**Precautionary statements**

P260	Do not breathe mist/vapours/spray.
P280	Wear protective gloves and eye/face protection.

**2.3. Other hazards**

No further relevant information available.

**SECTION 3: Composition/information on ingredients**

**3.2. Mixtures**

**Chemical characterization**

Mineral oil-based mixture. Mineral oil with DMSO extract < 3 % as measured by IP 346.

Revision date:  
17.06.2021

**BIZOL Leak and Smoke Stop+ o92**

Page 2 of 8

**Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
105-76-0	dibutyl maleate			25 - < 50 %
	203-328-4		01-2119523581-45	
	Skin Sens. 1, STOT RE 2; H317 H373			
64742-94-5	hydrocarbons, C10, aromatics, <1% naphthalene			10 - < 25 %
	918-811-1		01-2119463583-34	
	STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H336 H304 H411 EUH066			

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
105-76-0	203-328-4	dibutyl maleate	25 - < 50 %
		oral: LD50 = >= 3730 mg/kg	
64742-94-5	918-811-1	hydrocarbons, C10, aromatics, <1% naphthalene	10 - < 25 %
		oral: LD50 = > 6318,0 mg/kg	

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**General information**

When in doubt or if symptoms are observed, get medical advice. If unconscious but breathing normally, place in recovery position and seek medical advice. Remove contaminated, saturated clothing immediately.

**After inhalation**

Remove casualty to fresh air and keep warm and at rest.

**After contact with skin**

After contact with skin, wash immediately with plenty of water and soap.

**After contact with eyes**

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

**After ingestion**

If swallowed, rinse mouth with water (only if the person is conscious). Let water be drunken in little sips (dilution effect). Call a physician immediately. Do NOT induce vomiting.

**4.2. Most important symptoms and effects, both acute and delayed**

When in doubt or if symptoms are observed, get medical advice.

**4.3. Indication of any immediate medical attention and special treatment needed**

No information available.

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

**Suitable extinguishing media**

alcohol resistant foam, Extinguishing powder, Carbon dioxide (CO<sub>2</sub>).

**Unsuitable extinguishing media**

Full water jet.

**5.2. Special hazards arising from the substance or mixture**

Hazardous decomposition products: Carbon monoxide Carbon dioxide (CO<sub>2</sub>). Do not inhale explosion and combustion gases.

**5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

Revision date:  
17.06.2021

## BIZOL Leak and Smoke Stop+ o92

Page 3 of 8

### Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Do not allow to enter into soil/subsoil.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Protective measures: see section 7 + 8.

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Clean contaminated articles and floor according to the environmental legislation.

### 6.3. Methods and material for containment and cleaning up

#### Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

### 6.4. Reference to other sections

Protective measures: see section 7 + 8.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

Use personal protection equipment. Do not eat, drink or smoke when using this product. Provide fresh air. Handle and open container with care. Conditions to avoid: generation/formation of aerosols.

#### Advice on protection against fire and explosion

No special measures are necessary.

#### Advice on general occupational hygiene

When using do not eat, drink, smoke, sniff.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Protect against: Frost. Keep away from heat. Protect from direct sunlight. Keep container tightly closed in a cool, well-ventilated place.

### 7.3. Specific end use(s)

Observe technical data sheet.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Additional advice on limit values

- a no restriction
- b End of exposure or end of shift
- c at long-term exposure:
- d before next shift

Y: A risk of reproductive effects needs not to be feared if the occupational exposure limit value (AGW) and the biological limit value (BGW) is kept

Z: A risk of reproductive effects cannot to be excluded if the occupational exposure limit value (AGW) and the biological limit value (BGW) is kept

blood (B)  
Urine (U)

### 8.2. Exposure controls

#### Appropriate engineering controls

See section 7. No additional measures necessary.

#### Individual protection measures, such as personal protective equipment

Revision date:  
17.06.2021

**BIZOL Leak and Smoke Stop+ o92**

Page 4 of 8

**Eye/face protection**

Eye glasses with side protection.

**Hand protection**

Wear suitable gloves. Recommended glove articles: EN ISO 374. Suitable material: NBR (Nitrile rubber). Breakthrough time: > 480 min (Thickness of the glove material: 0.4 mm). Breakthrough times and swelling properties of the material must be taken into consideration. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

**Skin protection**

Protective clothing.

**Respiratory protection**

With correct and proper use, and under normal conditions, breathing protection is not required. When splashes or fine mist form, a permitted breathing apparatus suitable for these purposes must be used. Suitable respiratory protection apparatus: Filtering Half-face mask (EN 149), e.g. FFA P / FFP3.

**Environmental exposure controls**

Do not allow to enter into surface water or drains.

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	yellow
Odour:	characteristic

**Changes in the physical state**

Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	> 160 °C
Pour point:	not determined
Flash point:	> 61 °C
Lower explosion limits:	not determined
Upper explosion limits:	not determined
Auto-ignition temperature:	not determined
Decomposition temperature:	No information available.
pH-Value:	not determined
Viscosity / dynamic:	not determined
Viscosity / kinematic: (at 40 °C)	> 20,5 mm <sup>2</sup> /s
Flow time:	not determined
Water solubility:	insoluble
Partition coefficient n-octanol/water:	not determined
Vapour pressure:	not determined
Density (at 20 °C):	No data available
Bulk density:	not applicable
Relative vapour density:	not determined

**9.2. Other information**

**Other safety characteristics**

Evaporation rate:	not determined
-------------------	----------------

**Further Information**

No information available.

**SECTION 10: Stability and reactivity**

Revision date:  
17.06.2021

**BIZOL Leak and Smoke Stop+ o92**

Page 5 of 8

**10.1. Reactivity**

No information available.

**10.2. Chemical stability**

No information available.

**10.3. Possibility of hazardous reactions**

No hazardous reaction when handled and stored according to provisions.

**10.4. Conditions to avoid**

Heat.

**10.5. Incompatible materials**

No information available.

**10.6. Hazardous decomposition products**

No information available.

**SECTION 11: Toxicological information**

**11.1. Information on hazard classes as defined in GB CLP Regulation**

**Acute toxicity**

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
105-76-0	dibutyl maleate				
	oral	LD50 >= 3730 mg/kg	Rat		
64742-94-5	hydrocarbons, C10, aromatics, <1% naphthalene				
	oral	LD50 > 6318,0 mg/kg	Rat		

**Irritation and corrosivity**

Based on available data, the classification criteria are not met.

**Sensitising effects**

May cause an allergic skin reaction. (dibutyl maleate)

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure. (dibutyl maleate)

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**11.2. Information on other hazards**

**Other information**

Keeping to the general worker's protection rules and the industrial hygienics, there is no risk in handling this product through the personnel.

**SECTION 12: Ecological information**

**12.1. Toxicity**

There are no data available on the mixture itself.

**12.2. Persistence and degradability**

There are no data available on the mixture itself.

**12.3. Bioaccumulative potential**

There are no data available on the mixture itself.

**12.4. Mobility in soil**

No data available

Revision date:  
17.06.2021

## BIZOL Leak and Smoke Stop+ o92

Page 6 of 8

### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

### 12.7. Other adverse effects

No data available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### **Disposal recommendations**

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to EC directives 75/442/EEC and 91/689/EEC in the corresponding versions, covering waste and dangerous waste.

#### **List of Wastes Code - residues/unused products**

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated engine, gear and lubricating oils; hazardous waste

#### **List of Wastes Code - used product**

160708 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; wastes from transport tank, storage tank and barrel cleaning (except 05 and 13); wastes containing oil; hazardous waste

#### **Contaminated packaging**

Non-contaminated packages may be recycled. Consult the appropriate local waste disposal expert about waste disposal.

## SECTION 14: Transport information

### **Land transport (ADR/RID)**

<u>14.1. UN number or ID number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.

### **Marine transport (IMDG)**

<u>14.1. UN number or ID number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.

Marine pollutant: NO

### **Air transport (ICAO-TI/IATA-DGR)**

<u>14.1. UN number or ID number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.

### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

### 14.6. Special precautions for user

No data available

### 14.7. Maritime transport in bulk according to IMO instruments

No data available

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **EU regulatory information**

Revision date:  
17.06.2021

**BIZOL Leak and Smoke Stop+ o92**

Page 7 of 8

Restrictions on use (REACH, annex XVII):

Entry 3

2010/75/EU (VOC): 0 %  
Information according to 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

**National regulatory information**

Water hazard class (D): 2 - obviously hazardous to water

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information**

**Changes**

This data sheet contains changes from the previous version in section(s): 1,2,9,11,15.

**Abbreviations and acronyms**

- ADR: Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)
- RID: Règlement concernant le transport international ferroviaire des marchandises dangereuses (Regulations concerning the International Carriage of Dangerous Goods by Rail)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- ICAO: International Civil Aviation Organization
- CAS: Chemical Abstracts Service (a division of the American Chemical Society)
- DNEL/DMEL: Derived No-Effect Level / Derived Minimal Effect Level
- PNEC: Predicted No Effect Concentration
- WEL (UK): Workplace Exposure Limits
- TWA (EC): Time-Weighted Average
- STEL (EC): Short Term Exposure Limit
- ATE: Acute Toxicity Estimate
- LD50: Lethal Dose, 50% (median lethal dose)
- LC50: Lethal Concentration, 50% (median lethal concentration)
- EC50: half maximal Effective Concentration
- ErC50: EC50 in terms of reduction of growth rate
- AwSV: Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen

**Classification for mixtures and used evaluation method according to GB CLP Regulation**

Classification	Classification procedure
Skin Sens. 1; H317	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Chronic 3; H412	Calculation method

**Relevant H and EUH statements (number and full text)**

- H304 May be fatal if swallowed and enters airways.
- H317 May cause an allergic skin reaction.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

**Further Information**

Safety Data Sheet according to COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). -----

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Revision date:  
17.06.2021

**BIZOL Leak and Smoke Stop+ o92**

Page 8 of 8

---

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*