



**Bizol PTFE+ L50**

Revision date: 12.07.2017

Page 2 of 9

Results of PBT and vPvB assessment: not applicable.

**SECTION 3: Composition/information on ingredients**
**3.2. Mixtures**
**Chemical characterization**

Blend of the following materials with non-hazardous additives.

**Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
74-98-6	propane			12,5 - < 20 %
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1, Compressed gas; H220 H280			
	hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics			10 - < 12,5 %
	918-481-9		01-2119457273-39	
	Asp. Tox. 1; H304 EUH066			
75-28-5	isobutane			10 - < 12,5 %
	200-857-2	601-004-00-0	01-2119485395-27	
	Flam. Gas 1, Compressed gas; H220 H280			
106-97-8	butane			10 - < 12,5 %
	203-448-7	601-004-00-0	01-2119474691-32	
	Flam. Gas 1, Compressed gas; H220 H280			
109-66-0	pentane			10 - < 12,5 %
	203-692-4	601-006-00-1	01-2119459286-30	
	Flam. Liq. 1, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H224 H336 H304 H411 EUH066			

Full text of H and EUH statements: see section 16.

**SECTION 4: First aid measures**
**4.1. Description of first aid measures**
**General information**

When in doubt or if symptoms are observed, get medical advice. If unconscious place in recovery position and seek medical advice. Remove contaminated, saturated clothing immediately.

**After inhalation**

Remove casualty to fresh air and keep warm and at rest.

**After contact with skin**

After contact with skin, wash immediately with plenty of water and soap.

**After contact with eyes**

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

**After ingestion**

If swallowed, rinse mouth with water (only if the person is conscious). Let water be drunken in little sips (dilution effect). Call a physician immediately. Do NOT induce vomiting.

**4.2. Most important symptoms and effects, both acute and delayed**

When in doubt or if symptoms are observed, get medical advice.

**4.3. Indication of any immediate medical attention and special treatment needed**

No information available.

**SECTION 5: Firefighting measures**
**5.1. Extinguishing media**

**Bizol PTFE+ L50**

Revision date: 12.07.2017

Page 3 of 9

**Suitable extinguishing media**alcohol resistant foam, Extinguishing powder, Carbon dioxide (CO<sub>2</sub>).**Unsuitable extinguishing media**

High power water jet.

**5.2. Special hazards arising from the substance or mixture**Hazardous decomposition products: Carbon monoxide Carbon dioxide (CO<sub>2</sub>). Do not inhale explosion and combustion gases.**5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

**Additional information**

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Do not allow to enter into soil/subsoil.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

See protective measures under point 7 and 8.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Clean contaminated articles and floor according to the environmental legislation.

**6.3. Methods and material for containment and cleaning up**

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

**6.4. Reference to other sections**

See protective measures under point 7 and 8.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Use personal protection equipment. Do not eat, drink or smoke when using this product. Provide fresh air. Handle and open container with care. Conditions to avoid: generation/formation of aerosols.

**Advice on protection against fire and explosion**

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Vapours of flammable solvents can accumulate in the gas phase of closed container, especially during heat treatment. Therefore keep away from fire and sources of ignition. Provide earthing of containers, equipment, pumps and ventilation facilities. Use only non-sparking tools. Recommendation: Wear anti-static footwear and clothing

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Protect against: Frost. Keep away from heat. Protect against direct sunlight. Keep container tightly closed in a cool, well-ventilated place.

**7.3. Specific end use(s)**

Observe technical data sheet.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters**

## Bizol PTFE+ L50

Revision date: 12.07.2017

Page 4 of 9

### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
109-66-0	Pentane	600	1800		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL

### 8.2. Exposure controls

#### Appropriate engineering controls

See chapter 7. No additional measures necessary.

#### Protective and hygiene measures

When using do not eat, drink, smoke, sniff.

#### Eye/face protection

Eye glasses with side protection.

#### Hand protection

Wear suitable gloves. Recommended glove articles: DIN EN 374. Suitable material: NBR (Nitrile rubber). Breakthrough time (maximum wearing time): > 120 min (Thickness of the glove material: 0.4 mm). Breakthrough times and swelling properties of the material must be taken into consideration. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

#### Skin protection

Protective clothing.

#### Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Suitable respiratory protection apparatus: Filtering Half-face mask (DIN EN 149), e.g. FFA P / Full-/half-/quarter-face masks (DIN EN 136/140) + Combination filtering device (EN 14387), e.g. A P.

#### Environmental exposure controls

Do not allow to enter into surface water or drains.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state: Aerosol  
 Colour: light brown  
 Odour: characteristic

#### Test method

pH-Value: not determined

#### Changes in the physical state

Melting point: not determined

Initial boiling point and boiling range: not applicable

Pour point: not determined

Flash point: < 0 °C

#### Flammability

Solid: not applicable

Gas: not applicable

#### Explosive properties

The product is: not explosive. Heating causes rise in pressure with risk of bursting. In use, may form flammable/explosive vapour-air mixture.

Lower explosion limits: 0,6 vol. %

Upper explosion limits: 10,9 vol. %

Ignition temperature: > 200 °C

## Bizol PTFE+ L50

Revision date: 12.07.2017

Page 5 of 9

Decomposition temperature:	not determined
Vapour pressure: (at 20 °C)	8300 hPa
Density (at 20 °C):	0,68 g/cm <sup>3</sup>
Water solubility:	Immiscible
Partition coefficient:	not determined
Viscosity / dynamic:	not determined
Viscosity / kinematic:	not determined
Flow time:	not determined
Vapour density:	not determined
Evaporation rate:	not determined

### 9.2. Other information

Solid content: 34 %

No information available.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No information available.

### 10.2. Chemical stability

No information available.

### 10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

### 10.4. Conditions to avoid

Heat.

### 10.5. Incompatible materials

No information available.

### 10.6. Hazardous decomposition products

No information available.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name			
	Exposure route	Dose	Species	Source
	hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics			
	oral	LD50 >5000 mg/kg	Rat	
	dermal	LD50 >5000 mg/kg	Rabbit	
	inhalative (4 h) vapour	LC50 >4951 mg/l	Rat	
106-97-8	butane			
	inhalative (4 h) gas	LC50 658 ppm	Rat	GESTIS
109-66-0	pentane			
	inhalative (4 h) vapour	LC50 364 mg/l	Rat	GESTIS

#### Irritation and corrosivity

Based on available data, the classification criteria are not met.

#### Sensitising effects

Based on available data, the classification criteria are not met.

## Bizol PTFE+ L50

Revision date: 12.07.2017

Page 6 of 9

### **Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

### **STOT-single exposure**

Based on available data, the classification criteria are not met.

### **STOT-repeated exposure**

Repeated exposure may cause skin dryness or cracking.

### **Aspiration hazard**

Based on available data, the classification criteria are not met.

### **Practical experience**

### **Other observations**

Keeping to the general worker's protection rules and the industrial hygienics, there is no risk in handling this product through the personnel. Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

## SECTION 12: Ecological information

### **12.1. Toxicity**

There are no data available on the mixture itself.

CAS No	Chemical name				
	Aquatic toxicity	Dose	[h]   [d]	Species	Source
	hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics				
	Acute fish toxicity	LC50 >1000 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	OECD 203
	Acute algae toxicity	ErC50 >1000 mg/l	72 h	Pseudokirchneriella subcapitata	OECD 201
	Acute crustacea toxicity	EC50 >1000 mg/l	48 h	Daphnia magna (Big water flea)	OECD 202

### **12.2. Persistence and degradability**

There are no data available on the mixture itself.

### **12.3. Bioaccumulative potential**

There are no data available on the mixture itself.

### **Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
74-98-6	propane	2,36
75-28-5	isobutane	2,8
106-97-8	butane	2,89
109-66-0	pentane	3,39

### **12.4. Mobility in soil**

No data available

### **12.5. Results of PBT and vPvB assessment**

No data available

### **12.6. Other adverse effects**

No data available

## SECTION 13: Disposal considerations

### **13.1. Waste treatment methods**

#### **Advice on disposal**

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to EC directives 75/442/EEC and 91/689/EEC in the corresponding versions, covering waste and dangerous waste.

#### **Waste disposal number of waste from residues/unused products**

## Bizol PTFE+ L50

Revision date: 12.07.2017

Page 7 of 9

200113 MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS; separately collected fractions (except 15 01); solvents  
Classified as hazardous waste.

### Waste disposal number of contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

### Contaminated packaging

Non-contaminated packages may be recycled. Consult the appropriate local waste disposal expert about waste disposal.

## SECTION 14: Transport information

### Land transport (ADR/RID)

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -  
 Hazard label: 2.1



Classification code: 5F  
 Special Provisions: 190 327 344 625  
 Limited quantity: 1 L  
 Excepted quantity: E0  
 Transport category: 2  
 Tunnel restriction code: D

### Marine transport (IMDG)

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
 Hazard label: 2.1



Marine pollutant: NO  
 Special Provisions: 63, 190, 277, 327, 344, 959  
 Limited quantity: 1000 mL  
 Excepted quantity: E0  
 EmS: F-D, S-U

### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS, flammable  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
 Hazard label: 2.1



Special Provisions: A145 A167 A802  
 Limited quantity Passenger: 30 kg G

**Bizol PTFE+ L50**

Revision date: 12.07.2017

Page 8 of 9

Passenger LQ:	Y203
Excepted quantity:	E0
IATA-packing instructions - Passenger:	203
IATA-max. quantity - Passenger:	75 kg
IATA-packing instructions - Cargo:	203
IATA-max. quantity - Cargo:	150 kg

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: no

**14.6. Special precautions for user**

No data available

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

No data available

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 28: isobutane; butane

2010/75/EU (VOC): 65 % (438,8 g/l)

**National regulatory information**

Water contaminating class (D): 1 - slightly water contaminating

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information****Changes**

This data sheet contains changes from the previous version in section(s): 1,2,7,9,13,14,15.

**Abbreviations and acronyms**

ADR: Accord européen relatif au transport international des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
RID: Règlement concernant le transport international ferroviaire des marchandises dangereuses (Regulations concerning the International Carriage of Dangerous Goods by Rail)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
ICAO: International Civil Aviation Organization  
CAS: Chemical Abstracts Service (a division of the American Chemical Society)  
DNEL/DMEL: Derived No-Effect Level / Derived Minimal Effect Level  
PNEC: Predicted No Effect Concentration  
WEL (UK): Workplace Exposure Limits  
TWA (EC): Time-Weighted Average  
STEL (EC): Short Term Exposure Limit  
ATE: Acute Toxicity Estimate  
LD50: Lethal Dose, 50% (median lethal dose)  
LC50: Lethal Concentration, 50% (median lethal concentration)  
EC50: half maximal Effective Concentration  
ErC50: EC50 in terms of reduction of growth rate  
VwVwS: Verwaltungsvorschrift wassergefährdende Stoffe

**Relevant H and EUH statements (number and full text)**

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H224	Extremely flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.



### Bizol PTFE+ L50

Revision date: 12.07.2017

Page 9 of 9

H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

#### Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

---

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*