

Revision date:  
20.01.2021**BIZOL Pro CLP 150 Gear Oil**

Page 1 of 8

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

BIZOL Pro CLP 150 Gear Oil

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Lubricant

**1.3. Details of the supplier of the safety data sheet**

Company name:	BIZOL BITA Trading GmbH	
Street:	Martin-Buber-Str. 12	
Place:	D-14163 Berlin	
Telephone:	+49 (30) 804 869-0	Telefax: +49 (30) 804 869-2860
e-mail:	support@bizol.de	
Internet:	www.bizol.com	

**1.4. Emergency telephone number:**

Germany: +49 (30) 804 869-0 (08.00-17.00, Mo-Fr)  
In England and Wales: NHS Direct: 0845 4647 or 111 In Scotland: NHS 24 - 08454  
24 24 24 In Republic of Ireland: 01 809 2166

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Harmful to aquatic life with long lasting effects.

**2.2. Label elements****Regulation (EC) No. 1272/2008****Hazard statements**

H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements**

P273 Avoid release to the environment.

**2.3. Other hazards**

Results of PBT and vPvB assessment: not applicable.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****Chemical characterization**

Mineral oil-based mixture. Mineral oil with DMSO extract &lt; 3 % as measured by IP 346.

Revision date:  
20.01.2021

**BIZOL Pro CLP 150 Gear Oil**

Page 2 of 8

**Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
68955-53-3	amines, C12-14-tert-alkyl-			0.1 - < 0.3 %
	701-175-2		01-2119456798-18	
	Acute Tox. 2, Acute Tox. 3, Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1A, STOT SE 3, Aquatic Acute 1, Aquatic Chronic 1; H330 H311 H302 H314 H318 H317 H335 H400 H410			
1213789-63-9	C16-18-(even numbered, saturated and unsaturated)-alkylamines			< 0.1 %
	627-034-4		01-2119473797-19	
	Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Acute 1, Aquatic Chronic 1; H302 H314 H318 H335 H373 H304 H400 H410			

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
68955-53-3	701-175-2	amines, C12-14-tert-alkyl-	0.1 - < 0.3 %
	inhalation: LC50 = 1,19 mg/l (vapours); inhalation: ATE = 0,05 mg/l (dusts or mists); dermal: LD50 = 251 mg/kg; oral: LD50 = 612 mg/kg Skin Sens. 1A; H317: >= 10 - 100		
1213789-63-9	627-034-4	C16-18-(even numbered, saturated and unsaturated)-alkylamines	< 0.1 %
	oral: ATE = 500 mg/kg M akut; H400: M=10 M chron.; H410: M=10		

**SECTION 4: First aid measures**
**4.1. Description of first aid measures**
**General information**

When in doubt or if symptoms are observed, get medical advice. If unconscious but breathing normally, place in recovery position and seek medical advice. Remove contaminated, saturated clothing immediately.

**After inhalation**

Remove casualty to fresh air and keep warm and at rest.

**After contact with skin**

After contact with skin, wash immediately with plenty of water and soap.

**After contact with eyes**

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

**After ingestion**

If swallowed, rinse mouth with water (only if the person is conscious). Let water be drunk in little sips (dilution effect). Call a physician immediately. Do NOT induce vomiting.

**4.2. Most important symptoms and effects, both acute and delayed**

When in doubt or if symptoms are observed, get medical advice.

**4.3. Indication of any immediate medical attention and special treatment needed**

No information available.

**SECTION 5: Firefighting measures**
**5.1. Extinguishing media**
**Suitable extinguishing media**

alcohol resistant foam, Extinguishing powder, Carbon dioxide (CO<sub>2</sub>).

**Unsuitable extinguishing media**

Full water jet.

Revision date:  
20.01.2021**BIZOL Pro CLP 150 Gear Oil**

Page 3 of 8

**5.2. Special hazards arising from the substance or mixture**

Hazardous decomposition products: Carbon monoxide Carbon dioxide (CO<sub>2</sub>). Do not inhale explosion and combustion gases.

**5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

**Additional information**

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Do not allow to enter into soil/subsoil.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures****General measures**

Protective measures: see section 7 + 8.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Clean contaminated articles and floor according to the environmental legislation.

**6.3. Methods and material for containment and cleaning up****Other information**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

**6.4. Reference to other sections**

Protective measures: see section 7 + 8.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Use personal protection equipment. Do not eat, drink or smoke when using this product. Provide fresh air. Handle and open container with care. Conditions to avoid: generation/formation of aerosols.

**Advice on protection against fire and explosion**

No special measures are necessary.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Protect against: Frost. Keep away from heat. Protect from direct sunlight. Keep container tightly closed in a cool, well-ventilated place.

**7.3. Specific end use(s)**

Observe technical data sheet.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****8.2. Exposure controls****Appropriate engineering controls**

See section 7. No additional measures necessary.

**Protective and hygiene measures**

When using do not eat, drink, smoke, sniff.

**Eye/face protection**

Eye glasses with side protection.

**Hand protection**

Wear suitable gloves. Recommended glove articles: EN ISO 374. Suitable material: NBR (Nitrile rubber). Breakthrough time: > 480 min (Thickness of the glove material: 0.4 mm). Breakthrough times and swelling properties of the material must be taken into consideration. For special purposes, it is recommended to check

Revision date:  
20.01.2021

## BIZOL Pro CLP 150 Gear Oil

Page 4 of 8

the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

### Skin protection

Protective clothing.

### Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required. When splashes or fine mist form, a permitted breathing apparatus suitable for these purposes must be used. Suitable respiratory protection apparatus: Filtering Half-face mask (DIN EN 149), e.g. FFA P / FFP3.

### Environmental exposure controls

Do not allow to enter into surface water or drains.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	light brown	
Odour:	characteristic	
		<b>Test method</b>
pH-Value:		not applicable
<b>Changes in the physical state</b>		
Melting point:		not determined
Boiling point or initial boiling point and boiling range:		not determined
Pour point:		< -15 °C ASTM D 7346
Flash point:		> 210 °C EN ISO 2592
Lower explosion limits:		0,6 vol. %
Upper explosion limits:		6,5 vol. %
Auto-ignition temperature:		not determined
Decomposition temperature:		No information available.
Vapour pressure: (at 20 °C)		< 0,1 hPa
Density (at 15 °C):		0,9 g/cm <sup>3</sup> DIN EN ISO 12185
Water solubility:		insoluble
Partition coefficient n-octanol/water:		not determined
Viscosity / dynamic:		not determined
Viscosity / kinematic: (at 40 °C)		150 mm <sup>2</sup> /s ASTM D 7042
Flow time:		not determined
Relative vapour density:		not determined
Evaporation rate:		not determined

### 9.2. Other information

No information available.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No information available.

### 10.2. Chemical stability

No information available.

### 10.3. Possibility of hazardous reactions

Revision date:  
20.01.2021

**BIZOL Pro CLP 150 Gear Oil**

Page 5 of 8

No hazardous reaction when handled and stored according to provisions.

**10.4. Conditions to avoid**

Heat.

**10.5. Incompatible materials**

No information available.

**10.6. Hazardous decomposition products**

No information available.

**SECTION 11: Toxicological information**
**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**
**Acute toxicity**

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
68955-53-3	amines, C12-14-tert-alkyl-				
	oral	LD50 mg/kg	612	Rat	
	dermal	LD50 mg/kg	251	Rat	
	inhalation (4 h) vapour	LC50	1,19 mg/l	Rat - female	
	inhalation aerosol	ATE	0,05 mg/l		
1213789-63-9	C16-18-(even numbered, saturated and unsaturated)-alkylamines				
	oral	ATE mg/kg	500		

**Irritation and corrosivity**

Based on available data, the classification criteria are not met.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**11.2. Information on other hazards**
**Other information**

Keeping to the general worker's protection rules and the industrial hygienics, there is no risk in handling this product through the personnel.

**SECTION 12: Ecological information**
**12.1. Toxicity**

There are no data available on the mixture itself.

Revision date:  
20.01.2021

**BIZOL Pro CLP 150 Gear Oil**

Page 6 of 8

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
1213789-63-9	C16-18-(even numbered, saturated and unsaturated)-alkylamines					
	Acute fish toxicity	LC50	0,11 mg/l	96 h	Pimephales promelas (fathead minnow)	
	Acute crustacea toxicity	EC50	0,011 mg/l	48 h	Daphnia pulex (water flea)	
	Crustacea toxicity	NOEC	0,013 mg/l	21 d	Daphnia pulex (water flea)	

**12.2. Persistence and degradability**

There are no data available on the mixture itself.

**12.3. Bioaccumulative potential**

There are no data available on the mixture itself.

**BCF**

CAS No	Chemical name	BCF	Species	Source
1213789-63-9	C16-18-(even numbered, saturated and unsaturated)-alkylamines	500		

**12.4. Mobility in soil**

No data available

**12.5. Results of PBT and vPvB assessment**

No data available

**12.7. Other adverse effects**

No data available

**SECTION 13: Disposal considerations**
**13.1. Waste treatment methods**
**Disposal recommendations**

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to EC directives 75/442/EEC and 91/689/EEC in the corresponding versions, covering waste and dangerous waste.

**List of Wastes Code - residues/unused products**

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated engine, gear and lubricating oils; hazardous waste

**List of Wastes Code - used product**

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

**Contaminated packaging**

Non-contaminated packages may be recycled. Consult the appropriate local waste disposal expert about waste disposal.

**SECTION 14: Transport information**
**Land transport (ADR/RID)**
**14.1. UN number:**

No dangerous good in sense of this transport regulation.

**14.2. UN proper shipping name:**

No dangerous good in sense of this transport regulation.

**14.3. Transport hazard class(es):**

No dangerous good in sense of this transport regulation.

**14.4. Packing group:**

No dangerous good in sense of this transport regulation.

**Marine transport (IMDG)**

Revision date:  
20.01.2021**BIZOL Pro CLP 150 Gear Oil**

Page 7 of 8

<b>14.1. UN number:</b>	No dangerous good in sense of this transport regulation.
<b>14.2. UN proper shipping name:</b>	No dangerous good in sense of this transport regulation.
<b>14.3. Transport hazard class(es):</b>	No dangerous good in sense of this transport regulation.
<b>14.4. Packing group:</b>	No dangerous good in sense of this transport regulation.
Marine pollutant:	NO

**Air transport (ICAO-TI/IATA-DGR)**

<b>14.1. UN number:</b>	No dangerous good in sense of this transport regulation.
<b>14.2. UN proper shipping name:</b>	No dangerous good in sense of this transport regulation.
<b>14.3. Transport hazard class(es):</b>	No dangerous good in sense of this transport regulation.
<b>14.4. Packing group:</b>	No dangerous good in sense of this transport regulation.

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**14.6. Special precautions for user**

No data available

**14.7. Maritime transport in bulk according to IMO instruments**

No data available

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3

2010/75/EU (VOC): 0 %

Information according to 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

**National regulatory information**

Water hazard class (D): 1 - slightly hazardous to water

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information****Changes**

This data sheet contains changes from the previous version in section(s): 15.

**Abbreviations and acronyms**

ADR: Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement concernant le transport international ferroviaire des marchandises dangereuses (Regulations concerning the International Carriage of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

ICAO: International Civil Aviation Organization

CAS: Chemical Abstracts Service (a division of the American Chemical Society)

DNEL/DMEL: Derived No-Effect Level / Derived Minimal Effect Level

PNEC: Predicted No Effect Concentration

WEL (UK): Workplace Exposure Limits

TWA (EC): Time-Weighted Average

STEL (EC): Short Term Exposure Limit

ATE: Acute Toxicity Estimate

LD50: Lethal Dose, 50% (median lethal dose)

LC50: Lethal Concentration, 50% (median lethal concentration)

EC50: half maximal Effective Concentration

Revision date:  
20.01.2021**BIZOL Pro CLP 150 Gear Oil**

Page 8 of 8

ErC50: EC50 in terms of reduction of growth rate

AwSV: Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen

**Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]**

Classification	Classification procedure
Aquatic Chronic 3; H412	Calculation method

**Relevant H and EUH statements (number and full text)**

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

**Further Information**

Safety Data Sheet according to COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*