

**Safety Data Sheet**

according to UK REACH Regulation

**BIZOL Pro Gasoline System Clean p80**

Revision date: 14.04.2022

Product code: 100548

Page 1 of 13

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

BIZOL Pro Gasoline System Clean p80

UFI: Q0HX-V7DS-M00Y-JDGW

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Cleaning liquid for petrol system

**1.3. Details of the supplier of the safety data sheet**

Company name:	BIZOL Germany GmbH	
Street:	Martin-Buber-Str. 12	
Place:	D-14163 Berlin	
Telephone:	+49 30 804869 0	Telefax: +49 30 804 869 2860
e-mail:	support@bizol.de	
Internet:	www.bizol.com	

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GB CLP Regulation**

Flam. Liq. 3; H226  
Acute Tox. 4; H332  
Asp. Tox. 1; H304  
Skin Irrit. 2; H315  
Eye Dam. 1; H318  
STOT SE 3; H335  
STOT SE 3; H336  
STOT RE 2; H373  
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

**2.2. Label elements****GB CLP Regulation****Hazard components for labelling**

2-methylpropan-1-ol; iso-butanol  
xylene  
Hydrocarbons, C9-C11, n-Alkanes, Isoalkanes, Cyclenes, < 2% Aromates  
Hydrocarbons, C9-C11, Isoalkanes, Cycloalkanes, < 2% Aromates  
ethylbenzene

**Signal word:** Danger**Pictograms:****Hazard statements**

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H332	Harmful if inhaled.

**Safety Data Sheet**

according to UK REACH Regulation

**BIZOL Pro Gasoline System Clean p80**

Revision date: 14.04.2022

Product code: 100548

Page 2 of 13

H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

**Precautionary statements**

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P331	Do NOT induce vomiting.
P405	Store locked up.
P501	Dispose of this material and its container to hazardous or special waste collection point.

**2.3. Other hazards**

No information available.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures**

## Safety Data Sheet

according to UK REACH Regulation

**BIZOL Pro Gasoline System Clean p80**

Revision date: 14.04.2022

Product code: 100548

Page 3 of 13

**Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
78-83-1	2-methylpropan-1-ol; iso-butanol			20 - < 40 %
	201-148-0	603-108-00-1		
	Flam. Liq. 3, Skin Irrit. 2, Eye Dam. 1, STOT SE 3, STOT SE 3; H226 H315 H318 H335 H336			
1330-20-7	xylene			20 - < 40 %
	215-535-7	601-022-00-9		
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H226 H332 H312 H315 H319 H335 H373 H304			
64742-48-9	Hydrocarbons, C9-C11, n-Alkanes, Isoalkanes, Cyclenes, < 2% Aromates			10 - < 20 %
	919-857-5			
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1; H226 H336 H304 EUH066			
	Hydrocarbons, C9-C11, Isoalkanes, Cycloalkanes, < 2% Aromates			10 - < 20 %
	920-134-1		01-2119480153-44	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H336 H304 H411 EUH066			
100-41-4	ethylbenzene			1 - < 10 %
	202-849-4	601-023-00-4		
	Flam. Liq. 2, Acute Tox. 4, STOT RE 2, Asp. Tox. 1; H225 H332 H373 H304			
	Polyetheramine			1 - < 10 %
	Skin Irrit. 2, Eye Irrit. 2, Aquatic Chronic 2; H315 H319 H411			
108-88-3	toluene			< 0.1 %
	203-625-9	601-021-00-3		
	Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H225 H361d H315 H336 H373 H304			

Full text of H and EUH statements: see section 16.

**SECTION 4: First aid measures**
**4.1. Description of first aid measures**
**After inhalation**

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. Medical treatment necessary.

**After contact with skin**

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

**After contact with eyes**

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

**After ingestion**

Observe risk of aspiration if vomiting occurs.

**4.2. Most important symptoms and effects, both acute and delayed**

No information available.

**4.3. Indication of any immediate medical attention and special treatment needed**

**Safety Data Sheet**

according to UK REACH Regulation

**BIZOL Pro Gasoline System Clean p80**

Revision date: 14.04.2022

Product code: 100548

Page 4 of 13

Treat symptomatically.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

Carbon dioxide (CO<sub>2</sub>), Foam, Extinguishing powder. In case of fire, use sand, extinguishing powder or alcohol resistant foam.

**Unsuitable extinguishing media**

Water. Full water jet, Water

**5.2. Special hazards arising from the substance or mixture**

Flammable. Vapours can form explosive mixtures with air.

**5.3. Advice for firefighters**

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

**Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

**6.2. Environmental precautions**

Do not allow uncontrolled discharge of product into the environment. Explosion risk.

**6.3. Methods and material for containment and cleaning up**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

**6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Use personal protection equipment. This material is combustible and can be ignited by heat, sparks, flames, or other sources of ignition (e.g. static electricity, pilot lights, or mechanical/electrical equipment).

**Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.

Vapours can form explosive mixtures with air.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Hints on joint storage**

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances.

## Safety Data Sheet

according to UK REACH Regulation

### BIZOL Pro Gasoline System Clean p80

Revision date: 14.04.2022

Product code: 100548

Page 5 of 13

#### 7.3. Specific end use(s)

Cleaning liquid for petrol system

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
78-83-1	2-Methylpropan-1-ol	50	154		TWA (8 h)	WEL
		75	231		STEL (15 min)	WEL
100-41-4	Ethylbenzene	100	441		TWA (8 h)	WEL
		125	552		STEL (15 min)	WEL
108-88-3	Toluene	50	191		TWA (8 h)	WEL
		100	384		STEL (15 min)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

##### Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid (creatinine)	650 mmol/mol	urine	Post shift

#### 8.2. Exposure controls



##### Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

##### Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff.

##### Eye/face protection

Suitable eye protection: goggles.

##### Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

##### Skin protection

Use of protective clothing.

##### Respiratory protection

In case of inadequate ventilation wear respiratory protection.

## Safety Data Sheet

according to UK REACH Regulation

### BIZOL Pro Gasoline System Clean p80

Revision date: 14.04.2022

Product code: 100548

Page 6 of 13

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state: Liquid  
 Colour: clear, colourless  
 Odour: characteristic

#### Test method

pH-Value: not determined

#### Changes in the physical state

Melting point/freezing point: not determined

Boiling point or initial boiling point and boiling range: 118 °C

Flash point: 26 °C ISO 3679

#### Flammability

Solid: not applicable

Gas: not applicable

#### Explosive properties

The product is not: Explosive.

Lower explosion limits: 0,6 vol. %

Upper explosion limits: 11,3 vol. %

#### Self-ignition temperature

Solid: not applicable

Gas: not applicable

Decomposition temperature: not determined

#### Oxidizing properties

The product is not: oxidising.

Vapour pressure: 8 hPa  
 (at 20 °C)

Vapour pressure: 86 hPa DIN EN ISO 13016-1  
 (at 50 °C)

Density: 0,82 g/cm<sup>3</sup> DIN 12185

Water solubility: The study does not need to be conducted because the substance is known to be insoluble in water.

#### Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined

Relative vapour density: not determined

Evaporation rate: not determined

### 9.2. Other information

Solid content: not determined

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Flammable.

### 10.2. Chemical stability

**Safety Data Sheet**

according to UK REACH Regulation

**BIZOL Pro Gasoline System Clean p80**

Revision date: 14.04.2022

Product code: 100548

Page 7 of 13

The product is stable under storage at normal ambient temperatures.

**10.3. Possibility of hazardous reactions**

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

**10.4. Conditions to avoid**

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

**10.5. Incompatible materials**

Oxidising agent, strong; Acid, concentrated; Alkali (lye), concentrated

**10.6. Hazardous decomposition products**

Carbon monoxide Carbon dioxide

**SECTION 11: Toxicological information****11.1. Information on toxicological effects****Acute toxicity**

Harmful if inhaled.

**ATEmix calculated**

ATE (inhalation dust/mist) 3,951 mg/l

## Safety Data Sheet

according to UK REACH Regulation

**BIZOL Pro Gasoline System Clean p80**

Revision date: 14.04.2022

Product code: 100548

Page 8 of 13

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
78-83-1	2-methylpropan-1-ol; iso-butanol				
	oral	LD50 > 2830 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rat		
	inhalation (4 h) vapour	LC50 > 24 mg/l	Rat		
1330-20-7	xylene				
	oral	LD50 >2000 mg/kg	Rat		
	dermal	ATE 1100 mg/kg			
	inhalation vapour	ATE 11 mg/l			
	inhalation dust/mist	ATE 1,5 mg/l			
64742-48-9	Hydrocarbons, C9-C11, n-Alkanes, Isoalkanes, Cyclenes, < 2% Aromates				
	oral	LD50 >5000 mg/kg	Rat		
	dermal	LD50 >5000 mg/kg	Rabbit		
	inhalation (4 h) dust/mist	LC50 >5 mg/l	Rat		
	Hydrocarbons, C9-C11, Isoalkanes, Cycloalkanes, < 2% Aromates				
	oral	LD50 >5000 mg/kg	Rat	OECD 401	
	dermal	LD50 >5000 mg/kg	Rat	OECD 403	
	inhalation (4 h) dust/mist	LC50 >5 mg/l	Rat		
100-41-4	ethylbenzene				
	inhalation vapour	ATE 11 mg/l			
	inhalation dust/mist	ATE 1,5 mg/l			
	Polyetheramine				
	oral	LD50 >5000 mg/kg	Rat		
	dermal	LD50 >2000 mg/kg	Rabbit		
108-88-3	toluene				
	dermal	LD50 12200 mg/kg	Rabbit	GESTIS	
	inhalation (4 h) vapour	LC50 49 mg/l	Rat	GESTIS	

**Irritation and corrosivity**

Causes skin irritation.

Causes serious eye damage.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.



## Safety Data Sheet

according to UK REACH Regulation

### BIZOL Pro Gasoline System Clean p80

Revision date: 14.04.2022

Product code: 100548

Page 9 of 13

#### STOT-single exposure

May cause respiratory irritation. (2-methylpropan-1-ol; iso-butanol; xylene)  
 May cause drowsiness or dizziness. (2-methylpropan-1-ol; iso-butanol)

#### STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (xylene)

#### Aspiration hazard

May be fatal if swallowed and enters airways.

#### Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP]. Special hazards arising from the substance or mixture!

## SECTION 12: Ecological information

### 12.1. Toxicity

Harmful to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
78-83-1	2-methylpropan-1-ol; iso-butanol					
	Acute fish toxicity	LC50 mg/l	1430	96 h	Pimephales promelas	
	Acute algae toxicity	ErC50 mg/l	1250		Desmodesmus subspicatus	
	Acute crustacea toxicity	EC50 mg/l	1439	48 h	Daphnia magna	
64742-48-9	Hydrocarbons, C9-C11, n-Alkanes, Isoalkanes, Cyclenes, < 2% Aromates					
	Acute fish toxicity	LC50 mg/l	>1000	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute algae toxicity	ErC50 mg/l	>1000		Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50 mg/l	>1000	48 h	Daphnia magna (Big water flea)	
	Hydrocarbons, C9-C11, Isoalkanes, Cycloalkanes, < 2% Aromates					
	Acute fish toxicity	LC50	3,6 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	OECD 203
	Acute algae toxicity	ErC50 mg/l	1000	72 h	Pseudokirchneriella subcapitata	OECD 201
	Acute crustacea toxicity	EC50 46 mg/l	>22 - <	48 h	Daphnia magna (Big water flea)	OECD 202
108-88-3	toluene					
	Acute fish toxicity	LC50	13 mg/l	96 h	Carassius auratus	IUCLID
	Acute algae toxicity	ErC50 mg/l	12,5	72 h		GESTIS

### 12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
64742-48-9	Hydrocarbons, C9-C11, n-Alkanes, Isoalkanes, Cyclenes, < 2% Aromates			
		80%	28	
	Readily biodegradable (according to OECD criteria).			

## Safety Data Sheet

according to UK REACH Regulation

### BIZOL Pro Gasoline System Clean p80

Revision date: 14.04.2022

Product code: 100548

Page 10 of 13

#### 12.3. Bioaccumulative potential

The product has not been tested.

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
78-83-1	2-methylpropan-1-ol; iso-butanol	0,79
108-88-3	toluene	2,73

#### 12.4. Mobility in soil

The product has not been tested.

#### 12.5. Results of PBT and vPvB assessment

The product has not been tested.

#### 12.6. Other adverse effects

No information available.

#### Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### **Disposal recommendations**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

##### **List of Wastes Code - residues/unused products**

070104 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the manufacture, formulation, supply and use (MFSU) of basic organic chemicals; other organic solvents, washing liquids and mother liquors; hazardous waste

##### **List of Wastes Code - used product**

070104 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the manufacture, formulation, supply and use (MFSU) of basic organic chemicals; other organic solvents, washing liquids and mother liquors; hazardous waste

##### **Contaminated packaging**

Hazardous waste according to Directive 2008/98/EC (waste framework directive). Handle contaminated packages in the same way as the substance itself.

### SECTION 14: Transport information

#### **Land transport (ADR/RID)**

##### 14.1. UN number:

UN 1993

##### 14.2. UN proper shipping name:

FLAMMABLE LIQUID, N.O.S. (xylene; ethylbenzene; 2-methylpropan-1-ol; iso-butanol; Hydrocarbons, C9-C11, n-Alkanes, Isoalkanes, Cyclenes, &lt; 2% Aromates)

##### 14.3. Transport hazard class(es):

3

##### 14.4. Packing group:

III

Hazard label:

3



Classification code:

F1

Special Provisions:

274 601

Limited quantity:

5 L

Excepted quantity:

E1

## Safety Data Sheet

according to UK REACH Regulation

### BIZOL Pro Gasoline System Clean p80

Revision date: 14.04.2022

Product code: 100548

Page 11 of 13

Transport category: 3  
 Hazard No: 30  
 Tunnel restriction code: D/E

#### Inland waterways transport (ADN)

**14.1. UN number:** UN 1993  
**14.2. UN proper shipping name:** FLAMMABLE LIQUID, N.O.S. (xylene; ethylbenzene; 2-methylpropan-1-ol; iso-butanol; Hydrocarbons, C9-C11, n-Alkanes, Isoalkanes, Cycloalkanes, < 2% Aromates)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
 Hazard label: 3



Classification code: F1  
 Special Provisions: 274 601  
 Limited quantity: 5 L  
 Excepted quantity: E1

#### Marine transport (IMDG)

**14.1. UN number:** UN 1993  
**14.2. UN proper shipping name:** FLAMMABLE LIQUID, N.O.S. (xylene; ethylbenzene; 2-methylpropan-1-ol; iso-butanol; hydrocarbons, C9-C11, isoalkanes, cycloalkanes, < 2% aromates)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
 Hazard label: 3



Special Provisions: 223, 274, 955  
 Limited quantity: 5 L  
 Excepted quantity: E1  
 EmS: F-E, S-E

#### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number:** UN 1993  
**14.2. UN proper shipping name:** FLAMMABLE LIQUID, N.O.S. (xylene; ethylbenzene; 2-methylpropan-1-ol; iso-butanol; hydrocarbons, C9-C11, isoalkanes, cycloalkanes, < 2% aromates)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
 Hazard label: 3



Special Provisions: A3  
 Limited quantity Passenger: 10 L  
 Passenger LQ: Y344  
 Excepted quantity: E1  
 IATA-packing instructions - Passenger: 355

**Safety Data Sheet**

according to UK REACH Regulation

**BIZOL Pro Gasoline System Clean p80**

Revision date: 14.04.2022

Product code: 100548

Page 12 of 13

IATA-max. quantity - Passenger:	60 L
IATA-packing instructions - Cargo:	366
IATA-max. quantity - Cargo:	220 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**14.6. Special precautions for user**

Warning: Combustible liquid.

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

not applicable

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 40, Entry 48, Entry 75

Information according to 2012/18/EU P5c FLAMMABLE LIQUIDS  
(SEVESO III):**Additional information**

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC

**National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 3 - highly hazardous to water

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information****Abbreviations and acronyms**ADR: Accord européen sur le transport des marchandises dangereuses par Route  
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

UN: United Nations

DNEL: Derived No Effect Level

DMEL: Derived Minimal Effect Level

PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate

LL50: Lethal loading, 50%

EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate

**Safety Data Sheet**

according to UK REACH Regulation

**BIZOL Pro Gasoline System Clean p80**

Revision date: 14.04.2022

Product code: 100548

Page 13 of 13

NOEC: No Observed Effect Concentration  
 BCF: Bio-concentration factor  
 PBT: persistent, bioaccumulative, toxic  
 vPvB: very persistent, very bioaccumulative  
 RID: Regulations concerning the international carriage of dangerous goods by rail  
 ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)  
 EmS: Emergency Schedules  
 MFAG: Medical First Aid Guide  
 ICAO: International Civil Aviation Organization  
 MARPOL: International Convention for the Prevention of Marine Pollution from Ships  
 IBC: Intermediate Bulk Container  
 VOC: Volatile Organic Compounds  
 SVHC: Substance of Very High Concern  
 For abbreviations and acronyms, see table at <http://abbrev.esdscom.eu>

**Classification for mixtures and used evaluation method according to GB CLP Regulation**

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Acute Tox. 4; H332	Calculation method
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Calculation method
Eye Dam. 1; H318	Calculation method
STOT SE 3; H335	Calculation method
STOT SE 3; H336	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Chronic 3; H412	Calculation method

**Relevant H and EUH statements (number and full text)**

H225 Highly flammable liquid and vapour.  
 H226 Flammable liquid and vapour.  
 H304 May be fatal if swallowed and enters airways.  
 H312 Harmful in contact with skin.  
 H315 Causes skin irritation.  
 H318 Causes serious eye damage.  
 H319 Causes serious eye irritation.  
 H332 Harmful if inhaled.  
 H335 May cause respiratory irritation.  
 H336 May cause drowsiness or dizziness.  
 H361d Suspected of damaging the unborn child.  
 H373 May cause damage to organs through prolonged or repeated exposure.  
 H411 Toxic to aquatic life with long lasting effects.  
 H412 Harmful to aquatic life with long lasting effects.  
 EUH066 Repeated exposure may cause skin dryness or cracking.

**Further Information**

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*