

Revision date:  
29.04.2019**BIZOL Technology 5W-40 C3**

Page 1 of 8

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

BIZOL Technology 5W-40 C3

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Motor oil

**1.3. Details of the supplier of the safety data sheet**

|               |                         |                                |
|---------------|-------------------------|--------------------------------|
| Company name: | BIZOL BITA Trading GmbH |                                |
| Street:       | Martin-Buber-Str. 12    |                                |
| Place:        | D-14163 Berlin          |                                |
| Telephone:    | +49 (30) 804 869-0      | Telefax: +49 (30) 804 869-2860 |
| e-mail:       | support@bizol.de        |                                |
| Internet:     | www.bizol.com           |                                |

**1.4. Emergency telephone number:**

Germany: +49 (30) 804 869-0 (08.00-17.00, Mo-Fr)  
In England and Wales: NHS Direct: 0845 4647 or 111 In Scotland: NHS 24 - 08454 24 24 24 In Republic of Ireland: 01 809 2166

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

This mixture is not classified as hazardous in accordance with Regulation (EC) No. 1272/2008.

**2.2. Label elements****Regulation (EC) No. 1272/2008****Special labelling of certain mixtures**

|        |   |
|--------|---|
| EUH208 | Contains C14-16-18 alkylphenol. May produce an allergic reaction. |
| EUH210 | Safety data sheet available on request.                           |

**2.3. Other hazards**

Results of PBT and vPvB assessment: not applicable.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****Chemical characterization**

Mixture based on mineral oil and hydrocrack synthetic oil (DMSO extract &lt; 3 % as measured by IP 346).

Revision date:  
29.04.2019

## BIZOL Technology 5W-40 C3

Page 2 of 8

### Hazardous components

| CAS No       | Chemical name  |              |                  | Quantity      |
|--------------|--|--------------|------------------|---------------|
|              | EC No  | Index No     | REACH No         |               |
|              | GHS Classification                                     |              |                  |               |
| 64742-54-7   | distillates (petroleum), hydrotreated heavy paraffinic |              |                  | 25 - <= 100 % |
|              | 265-157-1  | 649-467-00-8 | 01-2119484627-25 |               |
|              | Asp. Tox. 1; H304                                      |              |                  |               |
| 64742-55-8   | distillates (petroleum), hydrotreated light paraffinic |              |                  | 1 - < 2.5 %   |
|              | 265-158-7  | 649-468-00-3 | 01-2119487077-29 |               |
|              | Asp. Tox. 1; H304                                      |              |                  |               |
| 36878-20-3   | bis(nonylphenyl)amine                                  |              |                  | 1 - < 2.5 %   |
|              | 253-249-4  |              | 01-2119488911-28 |               |
|              | Aquatic Chronic 4; H413                                |              |                  |               |
| 1190625-94-5 | C14-16-18 alkylphenol                                  |              |                  | 1 - < 2.5 %   |
|              | 931-468-2  |              | 01-2119498288-19 |               |
|              | Skin Sens. 1B, STOT RE 2; H317 H373                    |              |                  |               |

Full text of H and EUH statements: see section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

When in doubt or if symptoms are observed, get medical advice. If unconscious place in recovery position and seek medical advice. Remove contaminated, saturated clothing immediately.

#### After inhalation

Remove casualty to fresh air and keep warm and at rest.

#### After contact with skin

After contact with skin, wash immediately with plenty of water and soap.

#### After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

#### After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Let water be drunken in little sips (dilution effect). Call a physician immediately. Do NOT induce vomiting.

### 4.2. Most important symptoms and effects, both acute and delayed

When in doubt or if symptoms are observed, get medical advice.

### 4.3. Indication of any immediate medical attention and special treatment needed

No information available.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

alcohol resistant foam, Extinguishing powder, Carbon dioxide (CO<sub>2</sub>).

#### Unsuitable extinguishing media

Full water jet.

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products: Carbon monoxide Carbon dioxide (CO<sub>2</sub>). Do not inhale explosion and combustion gases.

### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Revision date:  
29.04.2019

**BIZOL Technology 5W-40 C3**

Page 3 of 8

**Additional information**

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Do not allow to enter into soil/subsoil.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

See protective measures under point 7 and 8.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Clean contaminated articles and floor according to the environmental legislation.

**6.3. Methods and material for containment and cleaning up**

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

**6.4. Reference to other sections**

See protective measures under point 7 and 8.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Use personal protection equipment. Do not eat, drink or smoke when using this product. Provide fresh air. Handle and open container with care. Conditions to avoid: generation/formation of aerosols.

**Advice on protection against fire and explosion**

No special measures are necessary.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Protect against: Frost. Keep away from heat. Protect against direct sunlight. Keep container tightly closed in a cool, well-ventilated place.

**7.3. Specific end use(s)**

Observe technical data sheet.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters**

Revision date:  
29.04.2019

## BIZOL Technology 5W-40 C3

Page 4 of 8

### DNEL/DMEL values

| CAS No                   | Substance  | Exposure route | Effect   | Value                  |
|--------------------------|--|----------------|----------|------------------------|
| 64742-54-7               | distillates (petroleum), hydrotreated heavy paraffinic |                |          |                        |
| Consumer DNEL, long-term |  | inhalation     | local    | 1,2 mg/m <sup>3</sup>  |
| Worker DNEL, long-term   |  | inhalation     | local    | 5,4                    |
| 36878-20-3               | bis(nonylphenyl)amine                                  |                |          |                        |
| Worker DNEL, long-term   |  | dermal         | systemic | 0,62 mg/kg bw/day      |
| Worker DNEL, long-term   |  | inhalation     | systemic | 4,37 mg/m <sup>3</sup> |
| Consumer DNEL, long-term |  | oral           | systemic | 0,31 mg/kg bw/day      |
| Consumer DNEL, long-term |  | dermal         | systemic | 0,31 mg/kg bw/day      |
| Consumer DNEL, long-term |  | inhalation     | systemic | 1,09 mg/m <sup>3</sup> |
| 1190625-94-5             | C14-16-18 alkylphenol                                  |                |          |                        |
| Worker DNEL, long-term   |  | inhalation     | systemic | 1,17 mg/m <sup>3</sup> |
| Worker DNEL, long-term   |  | dermal         | systemic | 0,3 mg/kg bw/day       |

### PNEC values

| CAS No              | Substance  | Value        |
|---------------------|--|--------------|
| 64742-54-7          | distillates (petroleum), hydrotreated heavy paraffinic |              |
| Secondary poisoning |  | 9,33 mg/kg   |
| 36878-20-3          | bis(nonylphenyl)amine                                  |              |
| Freshwater          |  | 0,1 mg/l     |
| Marine water        |  | 0,01 mg/l    |
| Freshwater sediment |  | 132000 mg/kg |
| Marine sediment     |  | 13200 mg/kg  |
| 1190625-94-5        | C14-16-18 alkylphenol                                  |              |
| Freshwater          |  | 0,1 mg/l     |
| Marine water        |  | 0,01 mg/l    |
| Freshwater sediment |  | 4266 mg/kg   |
| Marine sediment     |  | 422,6 mg/kg  |
| Soil                |  | 852,58 mg/kg |

## 8.2. Exposure controls

### Appropriate engineering controls

See chapter 7. No additional measures necessary.

### Protective and hygiene measures

When using do not eat, drink, smoke, sniff.

### Eye/face protection

Eye glasses with side protection.

### Hand protection

Wear suitable gloves. Recommended glove articles: EN ISO 374. Suitable material: NBR (Nitrile rubber). Breakthrough time (maximum wearing time): > 480 min (Thickness of the glove material: 0.4 mm). Breakthrough times and swelling properties of the material must be taken into consideration. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Revision date:  
29.04.2019

## BIZOL Technology 5W-40 C3

Page 5 of 8

### Skin protection

Protective clothing.

### Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required. When splashes or fine mist form, a permitted breathing apparatus suitable for these purposes must be used. Suitable respiratory protection apparatus: Filtering Half-face mask (DIN EN 149), e.g. FFA P / FFP3.

### Environmental exposure controls

Do not allow to enter into surface water or drains.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

|                 |                |
|-----------------|----------------|
| Physical state: | Liquid         |
| Colour:         | light brown    |
| Odour:          | characteristic |

|           |                |                    |
|-----------|----------------|--------------------|
| pH-Value: | not applicable | <b>Test method</b> |
|-----------|----------------|--------------------|

#### Changes in the physical state

|  |                           |                  |
|--|---------------------------|------------------|
| Melting point:                           | not determined            |                  |
| Initial boiling point and boiling range: | not determined            |                  |
| Pour point:                              | <= -27 °C                 | DIN ISO 3016     |
| Flash point:                             | >= 210 °C                 | EN ISO 2592      |
| Lower explosion limits:                  | 0,4 vol. %                |                  |
| Upper explosion limits:                  | 7,0 vol. %                |                  |
| Ignition temperature:                    | not determined            |                  |
| Decomposition temperature:               | No information available. |                  |
| Vapour pressure:<br>(at 20 °C)           | < 0,1 hPa                 |                  |
| Density (at 15 °C):                      | 0,85 g/cm <sup>3</sup>    | DIN EN ISO 12185 |
| Water solubility:                        | insoluble                 |                  |
| Partition coefficient:                   | not determined            |                  |
| Viscosity / dynamic:                     | not determined            |                  |
| Viscosity / kinematic:<br>(at 40 °C)     | 78 mm <sup>2</sup> /s     | ASTM D 7042      |
| Flow time:                               | not determined            |                  |
| Vapour density:                          | not determined            |                  |
| Evaporation rate:                        | not determined            |                  |

### 9.2. Other information

No information available.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No information available.

### 10.2. Chemical stability

No information available.

### 10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

### 10.4. Conditions to avoid

Heat.

Revision date:  
29.04.2019

**BIZOL Technology 5W-40 C3**

Page 6 of 8

**10.5. Incompatible materials**

No information available.

**10.6. Hazardous decomposition products**

No information available.

**SECTION 11: Toxicological information**
**11.1. Information on toxicological effects**
**Acute toxicity**

Based on available data, the classification criteria are not met.

| CAS No     | Chemical name  |                     |         |        |        |
|------------|--|---------------------|---------|--------|--------|
|            | Exposure route   | Dose                | Species | Source | Method |
| 64742-54-7 | distillates (petroleum), hydrotreated heavy paraffinic |                     |         |        |        |
|            | oral   | LD50 > 5000,0 mg/kg | Rat     |        |        |
|            | dermal   | LD50 > 5000,0 mg/kg | Rabbit  |        |        |

**Irritation and corrosivity**

Based on available data, the classification criteria are not met.

**Sensitising effects**

Contains C14-16-18 alkylphenol. May produce an allergic reaction.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Practical experience**
**Other observations**

Keeping to the general worker's protection rules and the industrial hygienics, there is no risk in handling this product through the personnel.

**SECTION 12: Ecological information**
**12.1. Toxicity**

There are no data available on the mixture itself.

**12.2. Persistence and degradability**

There are no data available on the mixture itself.

| CAS No     | Chemical name  |       |    |        |
|------------|--|-------|----|--------|
|            | Method   | Value | d  | Source |
|            | Evaluation   |       |    |        |
| 36878-20-3 | bis(nonylphenyl)amine                                  |       |    |        |
|            | OECD 301B  | 1 %   | 28 | ECHA   |
|            | Not readily biodegradable (according to OECD criteria) |       |    |        |

**12.3. Bioaccumulative potential**

There are no data available on the mixture itself.

**Partition coefficient n-octanol/water**

| CAS No     | Chemical name         | Log Pow |
|------------|-----------------------|---------|
| 36878-20-3 | bis(nonylphenyl)amine | 3,60    |

Revision date:  
29.04.2019**BIZOL Technology 5W-40 C3**

Page 7 of 8

**12.4. Mobility in soil**

No data available

**12.5. Results of PBT and vPvB assessment**

No data available

**12.6. Other adverse effects**

No data available

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Advice on disposal**

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to EC directives 75/442/EEC and 91/689/EEC in the corresponding versions, covering waste and dangerous waste.

**Waste disposal number of waste from residues/unused products**

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated engine, gear and lubricating oils; hazardous waste

**Contaminated packaging**

Non-contaminated packages may be recycled. Consult the appropriate local waste disposal expert about waste disposal.

**SECTION 14: Transport information****Land transport (ADR/RID)**

|   |  |
|---|--|
| <b><u>14.1. UN number:</u></b>                  | No dangerous good in sense of this transport regulation. |
| <b><u>14.2. UN proper shipping name:</u></b>    | No dangerous good in sense of this transport regulation. |
| <b><u>14.3. Transport hazard class(es):</u></b> | No dangerous good in sense of this transport regulation. |
| <b><u>14.4. Packing group:</u></b>              | No dangerous good in sense of this transport regulation. |

**Marine transport (IMDG)**

|   |  |
|---|--|
| <b><u>14.1. UN number:</u></b>                  | No dangerous good in sense of this transport regulation. |
| <b><u>14.2. UN proper shipping name:</u></b>    | No dangerous good in sense of this transport regulation. |
| <b><u>14.3. Transport hazard class(es):</u></b> | No dangerous good in sense of this transport regulation. |
| <b><u>14.4. Packing group:</u></b>              | No dangerous good in sense of this transport regulation. |
| Marine pollutant:                               | NO   |

**Air transport (ICAO-TI/IATA-DGR)**

|   |  |
|---|--|
| <b><u>14.1. UN number:</u></b>                  | No dangerous good in sense of this transport regulation. |
| <b><u>14.2. UN proper shipping name:</u></b>    | No dangerous good in sense of this transport regulation. |
| <b><u>14.3. Transport hazard class(es):</u></b> | No dangerous good in sense of this transport regulation. |
| <b><u>14.4. Packing group:</u></b>              | No dangerous good in sense of this transport regulation. |

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: no

**14.6. Special precautions for user**

No data available

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

No data available

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Revision date:  
29.04.2019**BIZOL Technology 5W-40 C3**

Page 8 of 8

**EU regulatory information**

2010/75/EU (VOC): 0 %  
Information according to 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

**National regulatory information**

Water contaminating class (D): 1 - slightly water contaminating

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information****Changes**

This data sheet contains changes from the previous version in section(s): 2,9,11,12,14,15.

**Abbreviations and acronyms**

ADR: Accord européen relatif au transport international des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
RID: Règlement concernant le transport international ferroviaire des marchandises dangereuses (Regulations concerning the International Carriage of Dangerous Goods by Rail)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
ICAO: International Civil Aviation Organization  
CAS: Chemical Abstracts Service (a division of the American Chemical Society)  
DNEL/DMEL: Derived No-Effect Level / Derived Minimal Effect Level  
PNEC: Predicted No Effect Concentration  
WEL (UK): Workplace Exposure Limits  
TWA (EC): Time-Weighted Average  
STEL (EC): Short Term Exposure Limit  
ATE: Acute Toxicity Estimate  
LD50: Lethal Dose, 50% (median lethal dose)  
LC50: Lethal Concentration, 50% (median lethal concentration)  
EC50: half maximal Effective Concentration  
ErC50: EC50 in terms of reduction of growth rate  
AwSV: Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen  
VwVwS: Verwaltungsvorschrift wassergefährdende Stoffe

**Relevant H and EUH statements (number and full text)**

H304 May be fatal if swallowed and enters airways.  
H317 May cause an allergic skin reaction.  
H373 May cause damage to organs (liver) through prolonged or repeated exposure.  
H413 May cause long lasting harmful effects to aquatic life.  
EUH208 Contains C14-16-18 alkylphenol. May produce an allergic reaction.  
EUH210 Safety data sheet available on request.

**Further Information**

Safety Data Sheet according to COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*